



Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

C.Scope Plastic Pipe Tracer 20m Product Code: C-SCOPE20



Information

The C.Scope Tracing Rod is an economical solution to the problem of tracing the route of plastic pipes and conduits. The tracing rod costs little and saves the contractor valuable time when the route of a plastic pipe needs to be determined quickly. The unique design is more resistant to kinks, less prone to breakage and yet smaller in diameter than any other rod of this type. Working in conjunction with the signal generator, the rod is inserted into the pipe and a traceable signal is sent either along the full length of the rod or only the tip. The transmitted signal may be easily traced using a C.Scope cable avoidance tool.

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.





Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

Features:

- Line tracing mode to allow the exact route of a pipe to be plotted.
- End tracing mode to enable blockages or tees to be pinpointed.
- Compact, lightweight and robust.
- Small diameter tracer rod to allow use within the smallest of service pipes.
- Flexible tracer rod allows progress around and beyond tight bends.
- Simple to operate.
- Suitable for use on live services under pressure.

SPECIFICATION

Product Name	20m and 50m Plastic Pipe Tracer (65' and 160')
Part No.	C-SCOPE50 and CSCOPE20
Frequency	Operates at 32,768Hz
Detection Depth Range:	
Line Detection Generator type and site conditions	3m (10 foot) dependent upon Locator and Signal
Tip Detection Generator type and site conditions	4m (13 foot) dependent upon Locator and Signal
Compatibility or 33/131kHz combined output	Any Signal Generator or Transmitter with 33kHz
Rod Length	20m or 50m (65' and 160')
Rod and Sonde Diameter	6mm (0.2")
Rod Minimum Bend Radius	50mm (1.9")
Construction:	
Reel	Robust plastic housing
Rod	Flexible, chemical resistant plastic

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.





Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

Reel dimensions (20m)	150 x 120 x 250mm (5.9" x 4.7" x 9.8")
Reel dimensions (50m)	165 x 290 x 240mm (6.5" x 11.4" x 9.4")
Reel weight (20m)	1248g (2 pound 12 ounces)
Reel weight (50m)	2073g (4 pound 8.5 ounces)
Operational Temperature Range	-20°C to 50°C (-4°F to 122°F)
Storage Temperature Range	-20°C to 50°C (-4°F to 122°F)
IP rating for actual Tracer Rod & Tip	68
IP rating for Plastic Pipe Tracer Casing	54

Availability: In Stock

£**POA**

Please enquire for the latest pricing & availability information for this item

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.

