

Double Outlet Hydrant Standpipe Product Code: 11705









Information

Used to obtain water from a pressurised mains supply via underground hydrants. The standard outlet for underground valve hydrants according to BS750 is 2 $\frac{1}{2}$ " BSRT (LRT) male, although hydrants are still in use with other non-standard outlet connections. Vernon Morris are able to supply hydrant standpipes with a range of non-standard base connections in all combinations, whether it be single or double outlet or whether you require 2" or 2 $\frac{1}{2}$ " DCV.

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.





Double Outlet Hydrant Standpipe

- High quality hydrant standpipe manufactured from aluminium alloy
- Swivel Head design
- Supplied with a standard 2 ½" female BSRT (LRT) inlet and twist release female instantaneous outlet

Availability: In Stock

£POA

Please enquire for the latest pricing & availability information for this item

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.



