



Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

VM Hydrant Flow Gauge c/w Black Case Product

Code: FGMETBC



Information

The VM Hydrant Flow Gauge is universally used by Water Engineers and Fire Service Authorities in the appraisal of piped water supply for fire fighting, development planning, and as a probe for investigating the ageing conditions of water mains and the consequence of overloading. In all of these applications, there is no better cost effective substitute

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2025 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.





Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

The flow rate indicator is of the manometer compressed-air type, incorporating a precision-bore glass tube. Used as an open water column, this measures all flows between 2.6 and 7.2 litres per second, purely by the gravimetric head, which measures velocity. Over the middle range (7.2 to 34 lps) the capacity of residual air within the glass tube and compression chamber is accurately determined at the top end by the entrapped water entering from the pitot tube. This tends to resist in accordance with Boyle's Law of the compressibility of gases.

A third range is provided, reading from 34 up to 60 lps. This is obtained by inserting a compensator plug into the chamber at the top of the manometer tube as well as fitting the compensation chamber between the manometer and pitot tube body. This increases the volumetric capacity.

One of the advantages of this device is that the calibration is permanent and cannot be affected by severe mechanical or hydraulic shock. Another advantage of the compressed-air manometer in this application is its virtually straight-line response to the square-law increment of velocity head. This gives an almost evenly spaced scale of calibration, and much greater clarity in reading the value of poor to indifferent flows at the lower end of the scale.

The Flow Gauge comes supplied in a polypropylene copolymer carry case which features:

- Watertight seal around the lid
- Waterproof and dustproof IP67 rated
- Easy to open double throw latches
- Load tested soft grip handle
- Holes for double padlocking
- Nylon hinge pins – corrosion free
- Temperature Rating -30/90°C

Availability: In Stock

£**POA**

Please enquire for the latest pricing & availability information for this item

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2025 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.





Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2025 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.

