



Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

Hydrant S.Pipe - D/O + 2 1/2"DCV Product Code:
11707



Information

Used to obtain water from a pressurised mains supply via underground hydrants. The standard outlet for underground valve hydrants according to BS750 is 2 1/2" BSRT (LRT) male, although hydrants are still in use with other non-standard outlet connections. Vernon Morris are able to supply hydrant standpipes with a range of non-standard base connections in all combinations, whether it be single or double outlet or whether you require 2" or 2 1/2" DCV.

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.





Vernon Morris Utility Solutions Ltd

Specialist Suppliers to the Utilities

2 ½" Double Check Valve (DCV) Double Outlet Hydrant Standpipe

- High quality Double outlet hydrant standpipe manufactured from aluminium alloy
- Swivel Head design
- Supplied with a standard 2 ½" female BSRT (LRT) inlet and twist release female instantaneous outlet
- Features a Full Flow 2 ½" Double Check Valve (DCV) to prevent water supply contamination

Availability: In Stock

£**POA**

Please enquire for the latest pricing & availability information for this item

Contact us

Vernon Morris Utility Solutions Ltd
Airfield View, Hawarden Industrial
Park, Deeside, Flintshire, CH5
3QW, United Kingdom
Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.

