

# Hydrant Standpipe 2" DCV (Double Pull - Plugin Head type) Product Code: 11710B





# Information

Used to obtain water from a pressurised mains supply via underground hydrants. The standard outlet for underground valve hydrants according to BS750 is 2  $\frac{1}{2}$ " BSRT (LRT) male, although hydrants are still in use with other non-standard outlet connections. Vernon Morris are able to supply hydrant standpipes with a range of non-standard base connections in all combinations, whether it be single or double outlet or whether you require 2" or 2  $\frac{1}{2}$ " DCV.

#### Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

## ©2025 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.







# 2" Double Check Valve (DCV) Hydrant Standpipe (Plug-in Head type)

- High quality hydrant standpipe manufactured from aluminium alloy
- Double Pull Plug-in Head type
- Supplied with a standard 2 ½" female BSRT (LRT) inlet and twist release female instantaneous outlet
- Features a 2" Double Check Valve (DCV) to prevent water supply contamination

Availability: In Stock

# **£POA**

Please enquire for the latest pricing & availability information for this item

#### Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

## ©2025 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.



