Hydrant Standpipe 2 1/2" DCV Product Code: 11710



Information

Used to obtain water from a pressurised mains supply via underground hydrants. The standard outlet for underground valve hydrants according to BS750 is 2 $\frac{1}{2}$ " BSRT (LRT) male, although hydrants are still in use with other non-standard outlet connections. Vernon Morris are able to supply hydrant standpipes with a range of non-standard base connections in all combinations, whether it be single or double outlet or whether you require 2" or 2 $\frac{1}{2}$ " DCV.

2 1/2" Double Check Valve (DCV) Hydrant Standpipe

- High quality hydrant standpipe manufactured from aluminium alloy
- Swivel Head design
- Supplied with a standard 2 ½" female BSRT (LRT) inlet and twist release female instantaneous outlet
- Features a Full Flow 2 ½" Double Check Valve (DCV) to prevent water supply contamination

Availability: In Stock

£POA

Please enquire for the latest pricing & availability information for this item

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.







Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

All information is correct at time of publishing, however we reserve the right to change any information at any time.



