VM

Mains Pressure Pump 121 lpm 20 Bar Product Code: VM125

Information

The Vernon Morris diaphragm type mains pressure test pump (VM125) is able to inject at a rate of 121 lpm to a maximum of 20 bar, which enables larger mains to be tested within an optimum timescale. This tough compact unit can easily be transported in a small van. The VM BP125 can be supplied with pressure and flow data capture equipment, enabling the facility of being able to produce a graph in Microsoft Excel to identify pipeline performance.

British Assessment Bureau — UKAS MANAGEMENT SYSTEMS 8289 — ISO 14001 ENVIRONMENTAL MANAGEMENT

British Assessment Bureau — UKAS MANAGEMENT SYSTEMS 8289 — ISO 9001 QUALITY MANAGEMENT

The VM125 mains pressure test pump is supplied with 6 metres of 1" suction hose complete with filter assembly.

The Vernon Morris mains pressure test pump can be supplied as:

• A stand-alone unit complete with 1" suction hose **(Part No. VM125)**

OR

• Pump complete with hoses and 2 contractors standpipes **(Part No. VM125A)**

The two contractors standpipes supplied are identified as follows:

• ¾" contractors standpipe complete with LRT base, DCV and hose union bib tap.

• ¾" contractors standpipe complete with ball valve and 2 x pressure points.

A 'Toughbook' field based laptop can also be supplied to compliment the package listed

above providing the capability of field based

Availability: In Stock

£**POA**

Please enquire for the latest pricing & availability information for this item