Tsurumi B-800 Drainage Pump - Auto 110v With Float Product Code: TS110APUMP



Information

The Tsurumi LB800 submersible water pump is both extremely robust and compact. Fitted with a 2 inch (50mm) outlet and a tough pressed steel strainer base and body. The pump has a 0.75kW motor and can be supplied in either 110v or 240v boasting excellent durability during periods of continuous use and/or operator abuse.

A combination of a rubber pump chamber, rubber wear plate and a urethane vortex impeller provides excellent wear resistance in site water applications that contain sand and silt in suspension, thus maintaining performance and reliability in the long term.

The Tsurumi LB-800 submersible pump utilises a 403 stainless steel shaft that is fitted with an ultra-hard-wearing twin mechanical seal (inboard: silicon carbide-silicon carbide) which runs in an oil chamber that has a patented oil lifter to maintain seal lubrication during operation in any position. This feature, combined with the water and air cooling route to the top outlet, allows the pump to operate for extended periods with little or no water.

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.





The Tsurumi LB-800 submersible pump can be supplied as a manual pump or as an automatic version with float switch.

	Impeller	Shaft seal	Level switch (automatic)			
LB	Semi-vortex	Double mechanical	Pendant, Agma or Sensor (optional)			

	Handle (110v / 230v)	Outlet (LB-480/800)	Outlet (LB-1500)		
	Resin/Steel & rubber	Cast aluminium	Cast iron		
Pump	Outer cover	Bearing housing	Pump casting		
	Steel	Cast aluminium	Rubber		
	Impeller (LB-480/800)	Impeller (LB-1500)	Suction cover (LB-480/800)		
	Urethane	Chromium iron	Steel & Urethane		
	Wear ring (LB-480/800)	Wear ring (LB-1500)	Shaft		
	Steel & Urethane	Rubber	S/S 410S		
	Shaft seal	Lubrication	Strainer		
	Silicon carbide	Oil	Steel		

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.

Level switch Pendant) Level switch (Agma) Level switch (Sensor)





Poles, protection

	Polypropylene	Polypropylene	Rubber & S/S 304
--	---------------	---------------	------------------

Insulation Thermal protection

Starting

	1 0103,	protectio	,	isalatio		illiai prote		ıtıng	
	2 pole, IP68		С	lass E	Inte	Integral		Internal capacitor	
Motor	Motor frame & head cover Cast aluminium			Pov	Power cable (10mtr) & switch cable				
				Rub	Rubber				
Model	Voltage	Outlet (mm)	kW	Flow (I/ min)	Head (mtrs)	Free Passage (mm)	Dia x H (mm)	Dry weight (kg)	Packing weight
LB-800	110V	50	0.75	310	15	6	Ø187x341	13	15.4
LB-800	230V	50	0.75	310	15	6	Ø187x341	13	15.4
LB-800 Auto	110V	50	0.75	310	15	6	Ø187x341	13.4	15.7
LB-800 Auto	230V	50	0.75	310	15	6	Ø187x341	13.4	15.7

Availability: In Stock

£POA

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.





Please enquire for the latest pricing & availability information for this item

Contact us

Vernon Morris Utility Solutions Ltd Airfield View, Hawarden Industrial Park, Deeside, Flintshire, CH5 3QW, United Kingdom Telephone: 01244 660794

©2024 Vernon Morris Utility Solutions Ltd.



